

L5203-BN / L5203-BP



Features

- 6mm (1/3 Type) Super HAD II CCD
- 620TV Lines
- Min. Illumination : 0.1 Lux @ Sens-up Off, F1.2 (Color)
0.00003 Lux @ Sens-up Auto, F1.2
- 3D-DNR
- Electronic Image Stabilization (EIS)
- Sens-up
- 4 User Color Modes
- Motion Detection
- 8 Privacy Zones Masking
- 3-Axis Mechanism

Specifications

Image Device	6mm (1/3 Type) Super HAD CCD
DSP	XDI-S2
Lens / Mount	2.8~11mm Vari-focal Lens, F1.2
Digital Zoom	x8
IRIS Control	DC
Sync. System	Internal
Horizontal Resolution	620 TV Lines
S/N Ratio	52dB
Minimum Illumination (30IRE)	0.06 Lux @ Sens-up OFF, F1.2 0.0001 Lux @ Sens-up Auto, F1.2
Video Output Signal	1Vp-p Composite (75 Ω)
Day & Night	Digital D&N (Day / Night / Auto)
Backlight Compensation	BLC / HSBC / Off
DNR	3D-DNR (Off / Low / Middle / High)
Motion Detection	4 Zones
Privacy Zone Masking	8 Mask Zones
Stabilizer(EIS)	On / Off
Multi OSD Language	15 Languages
Power Source	DC 12V / AC 24V (Dual Power)
Power Consumption	2.8W
Operating Temperature	-10°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	0% ~ 80%RH
Storage Humidity	0% ~ 85%RH
Weight	0.35 kg
Dimension (W x H)	Ø 140 x 91.7 mm